

Kylmämuotoillut U-profiilit

Cold roll-formed steel sections U-channels

Ainestandardi: S235J2G3 EN 10025

Mittastandardi: EN 10162

Pituus: 6 m

Koot	kg/m	Koodit
16 x 16 x 16 x 2	0,65	1102051900
20 x 20 x 20 x 2	0,84	1102051030
20 x 40 x 20 x 2	1,15	1102051920
25 x 25 x 25 x 2	1,07	1102051050
30 x 30 x 30 x 2	1,31	1102051070
30 x 30 x 30 x 3	1,89	1102051110
35 x 35 x 35 x 2	1,54	1102052000
25 x 50 x 25 x 3	2,12	1102052020
30 x 60 x 30 x 3	2,59	1102052040
30 x 100 x 30 x 3	3,53	1102052060
35 x 35 x 35 x 3	2,24	1102051130
35 x 50 x 35 x 3	2,59	1102052100
40 x 40 x 40 x 2	1,78	1102052120
40 x 40 x 40 x 3	2,59	1102051150
40 x 50 x 40 x 3	2,83	1102052160
40 x 70 x 40 x 3	3,30	1102052180
40 x 60 x 40 x 3	3,06	1102101390
50 x 50 x 50 x 3	3,30	1102051210
40 x 80 x 40 x 3	3,53	1102052240
40 x 80 x 40 x 4	4,61	1102101490
40 x 80 x 40 x 5	5,55	1102052280
40 x 120 x 40 x 4	5,87	1102052300
50 x 100 x 50 x 4	5,87	1102101570
50 x 100 x 50 x 5	7,12	1102101620
50 x 120 x 50 x 4	6,49	1102051641
60 x 120 x 60 x 4	7,12	1102101680
60 x 120 x 60 x 6	10,25	1102101700
60 x 140 x 60 x 6	11,19	1102101740
60 x 160 x 60 x 5	10,26	1102052410
60 x 160 x 60 x 6	12,13	1102101770
60 x 200 x 60 x 6	14,02	1102052440
70 x 140 x 70 x 4	8,38	1102052460
70 x 140 x 70 x 5	10,26	1102052480
70 x 160 x 70 x 6	13,08	1102052500
70 x 180 x 70 x 6	14,02	1102052520
70 x 200 x 70 x 6	14,96	1102052540
75 x 250 x 75 x 6	17,79	1102052560

Kylmämuotoillut L-profiilit

Cold roll-formed steel sections L-channels

Ainestandardi: S235J2G3 EN 10025

Mittastandardi: EN 10162

Pituus: 6 m

	Koot	kg/m	Koodit
KULMA KY-MUOT.	15 x 15 x 2	0,42	1102002400
KULMA KY-MUOT.	20 x 20 x 2	0,58	1102002420
KULMA KY-MUOT.	25 x 25 x 2	0,73	1102002440
KULMA KY-MUOT.	30 x 30 x 2	0,89	1102002460
KULMA KY-MUOT.	30 x 30 x 3	1,30	1102002150
KULMA KY-MUOT.	40 x 40 x 2	1,20	1102002500
KULMA KY-MUOT.	40 x 40 x 3	1,77	1102002520
KULMA KY-MUOT.	50 x 50 x 3	2,24	1102002540
KULMA KY-MUOT.	60 x 60 x 3	2,71	1102002560
KULMA KY-MUOT.	70 x 70 x 5	5,13	1102002580
KULMA KY-MUOT.	75 x 75 x 4	4,50	1102002600
KULMA KY-MUOT.	80 x 80 x 5	5,91	1102002620
KULMA KY-MUOT.	40 x 20 x 2	0,89	1102002640
KULMA KY-MUOT.	50 x 30 x 3	1,77	1102002660
KULMA KY-MUOT.	60 x 30 x 3	2,00	1102002680
KULMA KY-MUOT.	60 x 40 x 3	2,24	1102002700
KULMA KY-MUOT.	70 x 50 x 4	3,56	1102002720
KULMA KY-MUOT.	100 x 50 x 4	4,50	1102002740
KULMA KY-MUOT.	125 x 65 x 5	7,09	1102002760
KULMA KY-MUOT.	150 x 50 x 5	7,48	1102002780

Kylmämuotoillut Z-, C-profiilit

Z-, C-sections

Ainestandardi: S235J2G3 EN 10025

Mittastandardi: EN 10162

Pituus: 6 m

	Koot	kg/m	Koodit
Z-TERÄS	30 x 53 x 40 x 3	2,66	1102103800
C-PROFIILI NO 1	(C 50 x 30 x 14 x 3)	2,78	1102103820
KANNATUSKISKO C4	(C 30 x 30 x 20 x 2)	1,47	1102103840
C-PROF. NRO 5	(C 28 x 15 x 8 x 2)	0,95	1102103860
C-PROF. NRO 7	(30 x 30 x 10 x 2)	1,52	1102103880