

Lattatangot

Sinkopuhallettuna ja suojamaalattuna/KORRO SS (16 µm ± 5 µm)

Flat bars

Shot-blasting and protective coating/KORRO SS (16 µm ± 5 µm)

S235 JR

Ainestandardi: EN 10025

Ainestodistus: EN 10204: 2.2

Mittastandardi: EN 10058

Pituus: 6 m

Mitat	kg/m	Koodit
5 x 30	1,18	1100102425
5 x 40	1,57	1100102430
5 x 50	1,96	1100102435
6 x 40	1,88	1100102440
6 x 50	2,36	1100102445
6 x 60	2,83	1100102450
8 x 40	2,51	1100102455
8 x 60	3,77	1100102465
8 x 80	5,02	1100102470
10 x 40	3,14	1100102475
10 x 50	3,93	1100102480
10 x 60	4,71	1100102485
10 x 100	7,85	1100102490

Kulmatangot

Sinkopuhallettuna ja suojamaalattuna/KORRO SS (16 µm ± 5 µm)

Angles

Shot-blasting and protective coating/KORRO SS (16 µm ± 5 µm)

S235 JR

Ainestandardi: EN 10025

Ainestodistus: EN 10204: 2.2

Mittastandardi: EN 10056

Pituus: 6 m

Mitat	kg/m	Koodit
20 x 20 x 3	0,88	1100401920
30 x 30 x 3	1,36	1100401925
30 x 30 x 4	1,78	1100401930
40 x 40 x 4	2,42	1100401935
50 x 50 x 5	3,77	1100401940
60 x 60 x 6	5,42	1100401945
80 x 80 x 8	9,66	1100401950

U-palkit

Sinkopuhallettuna ja suojamaalattuna/KORRO SS (16 µm ± 5 µm)
 UNP beams
 Shot-blasting and protective coating/KORRO SS (16 µm ± 5 µm)
 S235 JR

Ainestandardi: EN 10025
 Mittastandardi: EN 10279

Ainestodistus: EN 10204: 2.2
 Pituus: 6 m

Mitat	kg/m	Koodit
50	5,59	1101101740
65	7,09	1101101742
80	8,64	1101101743
100	10,60	1101101744
120	13,40	1101101745
140	16,00	1101101746
160	18,80	1101101747

Putkipalkit

Sinkopuhallettuna ja suojamaalattuna/KORRO SS (16 µm ± 5 µm)
 SHS/RHS
 Shot-blasting and protective coating/KORRO SS (16 µm ± 5 µm)
 S355 J2 H

Ainestandardi: EN 10219 KYVA
 Mittastandardi: EN 10219 KYVA

Ainestodistus: EN 10204: 3.1
 Pituus: 6 m = muut
 12 m = 150 x 150 x 5 mm

Neliöt
 Squares

Mitat	kg/m	Koodit
30 x 30 x 3	2,36	1200201000
40 x 40 x 3	3,30	1200201010
40 x 40 x 4	4,20	1200201020
50 x 50 x 3	4,25	1200201030
50 x 50 x 4	5,45	1200201410
60 x 60 x 3	5,19	1200201050
80 x 80 x 5	11,30	1200201060
100 x 100 x 3	8,96	1200201070
100 x 100 x 4	11,70	1200202490

Suorakaiteet
 Rectangulars

Mitat	kg/m	Koodit
50 x 30 x 3	3,30	1200211200
50 x 30 x 4	4,20	1200211205
60 x 40 x 3	4,25	1200211210
60 x 40 x 4	5,45	1200211220
80 x 40 x 3	5,19	1200211422
80 x 40 x 4	6,71	1200211240
100 x 50 x 3	6,60	1200211250
100 x 50 x 4	8,59	1200211260
100 x 50 x 5	10,50	1200211270

Putket

Sinkopuhallettuna ja suojamaalattuna/KORRO SS (16 µm ± 5 µm)

Pipes

Shot-blasting and protective coating/KORRO SS (16 µm ± 5 µm)

S235

Ainestandardi: EN 2458

Ainestodistus: EN 10204: 2.2

Mittastandardi: EN 1615

Pituus: 6 m

Mitat	kg/m	Koodit
26,9 x 2,65	1,60	1203001000
33,7 x 2,5	1,92	1203001010
42,4 x 2,5	2,46	1203001020
48,3 x 2,5	2,82	1203001030